Granor Rubber & Engineering

Chemwatch: 4602-39

Version No: 7.1 Print Date: 30/09/2022 Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements L.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier	
Product name	Dow Corning 902 RCS Part B
Chemical Name	Not Applicable
Synonyms	Not Available
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Mixed with part A to form a silicone rubber sealant.	

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Granor Rubber & Engineering	
Address	Reid Street Bayswater VIC 3153 Australia	
Telephone	+61 3 9762 9699	
Fax	+61 3 9762 9611	
Website	Not Available	
Email	Not Available	

Emergency telephone number

Association / Organisation	Poisons Information Centre	
Emergency telephone numbers	13 11 26	
Other emergency telephone numbers	Not Available	

SECTION 2 Hazards identification

Poisons Schedule	Not Applicable
Classification [1]	Serious Eye Damage/Eye Irritation Category 2B
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Hazard pictogram(s)	Not Applicable
Signal word	Warning

Hazard statement(s)

H320 Causes eye irritation.

Precautionary statement(s) Prevention

P264	Wash all exposed external body areas thoroughly after handling.
F204	wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313 If eye irritation persists: Get medical advice/attention.		

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Chemwatch Hazard Alert Code: 1

Issue Date: 30/09/2022

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
63148-62-9	40-70	polydimethylsiloxane
Not Available	30-60	calcium carbonate treated with stearic acid
70131-67-8	10-30	dimethylsiloxane, hydroxy-terminated
Legend:	d: 1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with strong oxidising agents as ignition may result			
vice for firefighters				
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. 			
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. High temperature decomposition products include silicon dioxide, small amounts of formaldehyde, formic acid, acetic acid and traces of silicon polymers. These gases may ignite and, depending on circumstances, may cause the resin/polymer to ignite. An outer skin of silica may also form. Extinguishing of fire, beneath the skin, may be difficult. 			
HAZCHEM	Not Applicable			

SECTION 6 Accidental release measures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Slippery when spilt. , Clean up all spills immediately. Avoid contact with skin and eyes. Wipe up and absorb small quantities with vermiculite or other absorbent material. , Place in suitable containers for disposal.
Major Spills	Slippery when spilt. , Alert Fire Brigade and tell them location and nature of hazard. Wear protective clothing, impervious gloves and safety glasses. Prevent, by any means available, spillage from entering drains or water courses. , Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling Absorb remaining product with sand, earth or vermiculite. Collect residues and seal in labelled drums for disposal If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	 Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. When handling DO NOT eat, drink or smoke. Always wash hands with soap and water after handling. Avoid physical damage to containers. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS.
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid storage with oxidisers

SECTION 8 Exposure controls / personal protection

Control parameters

- Occupational Exposure Limits (OEL)
- INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
polydimethylsiloxane	65 mg/m3	720 mg/m3		4,300 mg/m3
dimethylsiloxane, hydroxy- terminated	190 mg/m3	2,100 mg/m3		13,000 mg/m3
Ingredient	Original IDLH		Revised IDLH	
polydimethylsiloxane	Not Available		Not Available	
dimethylsiloxane, hydroxy- terminated	Not Available		Not Available	

MATERIAL DATA

Exposure controls

Appropriate engineering

Page 4 of 8

Dow Corning 902 RCS Part B

controls	Refer also to protective measures for the other component used with the product. Read both SDS before using; store and attach SDS together.
Personal protection	
Eye and face protection	 Safety glasses with side shields; or as required, Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]
Skin protection	See Hand protection below
Hands/feet protection	 Barrier cream PVC gloves Rubber gloves Safety footwear
Body protection	See Other protection below
Other protection	Overalls ▶ Eyewash unit.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P2	-
up to 50	1000	-	A-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P2
up to 100	10000	-	A-3 P2
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	White viscous liquid with an amine-like odour; does not mix with water.		
Physical state	Liquid	Relative density (Water = 1)	1.30
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	150000
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>101.1 (CC)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7		
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. 		
Possibility of hazardous reactions	See section 7		
Conditions to avoid	See section 7		
Incompatible materials	See section 7		
Hazardous decomposition products	See section 5		

SECTION 11 Toxicological information

Inhaled	When heated at high temperatures inhalation of fumes and oxidation products from methyl silicones can be irritating and toxic. Massive exposures to vapours of heated silicone oil can depress nervous system and may even cause death. Not normally a hazard due to non-volatile nature of product Inhalation of vapour is more likely at higher than normal temperatures.		
Ingestion	Swallowing large amounts may produce nausea and have a laxative effect. Ingestion may result in nausea, abdominal irritation, pain and vomiting		
	Smoothing the sealant with saliva wet finger may introduc	e sealant into the mouth. Safer alternates should replace this poor work practice.	
Skin Contact	Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.		
Eye	Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.		
Chronic	Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in ar form, should be avoided by observing good occupational work practice.		
	τοχιςιτγ	IRRITATION	
Dow Corning 902 RCS Part B	Not Available	Not Available	
	τοχιςιτγ	IRRITATION	
polydimethylsiloxane	Dermal (rabbit) LD50: >3000 mg/kg ^[2]	Eye (rabbit): 100 mg/1h - mild	
	Oral (Rat) LD50; >35000 mg/kg ^[2]		
	τοχιςιτγ	IRRITATION	
dimethylsiloxane, hydroxy-	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Not Available	
terminated	Oral (Rat) LD50; >5000 mg/kg ^[2]		
Legend:	1. Value obtained from Europe ECHA Registered Substan specified data extracted from RTECS - Register of Toxic I	nces - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise Effect of chemical Substances	
POLYDIMETHYLSILOXANE	non-sensitising in human patch test. [Xerox]*	ion toxicity studies The no observable effect level is 450 mg/m3. Non-irritating and ontact causing inflammation. Repeated or prolonged exposure to irritants may produce	
DIMETHYLSILOXANE, HYDROXY-TERMINATED	* [Mobay Chemical Corp] **[GE]		
	Some studies indicate that some of the siloxanes may have the possible effects of the siloxanes on humans and the e Only few siloxanes are described in the literature with reg	m to be problematic are acute toxicity, irritant effects, sensitization and genotoxicity. ve endocrine disrupting properties, and reproductive effects have caused concern about nvironment. ard to health effects, and it is therefore not possible to make broad conclusions and and cyclic siloxanes based on the present evaluation. Data are primarily found on the	

and D5 (decamethylcyclopentasiloxane) and the short-linear HMDS (hexamethyldisiloxane).

POLYDIMETHYLSILOXANE & DIMETHYLSILOXANE, These three siloxanes have a relatively low order of acute toxicity by oral, dermal and inhalatory routes and do not require classification for this HYDROXY-TERMINATED effect.

They are not found to be irritating to skin or eyes and are also not found sensitizing by skin contact. Data on respiratory sensitization have not been identified.

Subacute and subchronic toxicity studies show that the liver is the main target organ for D4 which also induces liver cell enzymes. This enzyme induction contributes to the elimination of the substance from the tissues. Primary target organ for D5 exposure by inhalation is the lung. D5 has an enzyme induction profile similar to that of D4. Subacute and subchronic inhalation of HMDS affect in particular the lungs and kidneys in rats. None of the investigated siloxanes show any signs of genotoxic effects in vitro or in vivo. Preliminary results indicate that D5 has a potential carcinogenic effect.

Dow Corning 902 RCS Part	В
--------------------------	---

	D4 is considered to impair fertility in rats by inhalation and is classified as a substance toxic to reproduction in category 3 with the risk phrase R62 ('Possible risk of impaired fertility'). The results of a study to screen for oestrogen activity indicate that D4 has very weak oestrogenic and antioestrogenic activity and is a partial agonist (enhances the effect of the estrogen). It is not uncommon for compounds that are weakly oestrogenic to also have antioestrogenic properties. Comparison of the oestrogenic potency of D4 relative to ethinyloestradiol (steroid hormone) indicates that D4 is 585,000 times less potent than ethinyloestradiol in the rat stain Sprague- Dawley and 3.7 million times less potent than ethinyloestradiol in the Fisher-344 rat strain. Because of the lack of effects on other endpoints designated to assess oestrogenicity, the oestrogenicity as mode of action for the D4 reproductive effects has been questioned. An indirect mode of action causing a delay of the LH (luteinising hormone) surge necessary for optimal timing of ovulation has been suggested as the mechanism. Based on the reviewed information, the critical effects of the siloxanes are impaired fertility (D4) and potential carcinogenic effects (uterine tumours in females). Furthermore there seem to be some effects on various organs following repeated exposures, the liver (D4), kidney (HMDS) and lung (D5 and HMDS) being the target organs. A possible oestrogenic effect contributing to the reproductive toxicity of D4 is debated. There seems however to be some indication that this toxicity may be caused by another mechanism than oestrogen activity. Studies are available for linear siloxanes from an analogue group comprising di- to hexa- siloxanes, as well as key physicochemical properties, The results of the acute toxicity studies for this analogue group are in agreement: there is no evidence from any of the available studies that the substances in this group have any potential for acute toxicity (in terms of either lethality or advers		
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	¥	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×

X – Data either not available or does not fill the criteria for classification v – Data available to make classification

SECTION 12 Ecological information

Toxicity

Dow Corning 902 RCS Part B	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
polydimethylsiloxane	Not Available	Not Available	Not Available	Not Available	Not Available
dimethylsiloxane, hydroxy- terminated	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Ecotox databa		IA Registered Substances - Ecotoxicological In quatic Hazard Assessment Data 6. NITE (Japa		

DO NOT discharge into sewer or waterways.

Persistence and degradability

	,	
Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients
Bioaccumulative potential		
Ingredient	Bioaccumulation	
	No Data available for all ingredients	
Mobility in soil		
Ingredient	Mobility	

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.

 Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill. 		
SECTION 14 Transport information		
Labels Required		

Marine Pollutant	NO
HAZCHEM	Not Applicable
Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS	
Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not	App	licat	ble
-----	-----	-------	-----

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
polydimethylsiloxane	Not Available
dimethylsiloxane, hydroxy- terminated	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
polydimethylsiloxane	Not Available
dimethylsiloxane, hydroxy- terminated	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

polydimethylsiloxane is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 10 / Appendix C

Australian Inventory of Industrial Chemicals (AIIC)

Australian Inventory of Industrial Chemicals (AIIC)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 4

dimethylsiloxane, hydroxy-terminated is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 10 / Appendix C Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 4

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (polydimethylsiloxane; dimethylsiloxane, hydroxy-terminated)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP No (polydimethylsiloxane; dimethylsiloxane, hydroxy-terminated)		
Japan - ENCS No (polydimethylsiloxane; dimethylsiloxane, hydroxy-terminated)		
Korea - KECI Yes		
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA Yes		
Taiwan - TCSI Yes		
Mexico - INSQ Yes		
Vietnam - NCI	ietnam - NCI Yes	
Russia - FBEPH	Yes	
Legend: Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	30/09/2022
Initial Date	26/06/2001

SDS Version Summary

Version	Date of Update	Sections Updated
6.1	29/08/2019	Physical Properties
7.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

